USGS STM SENSOR RECOVERY FORM (one form per housing) DATE: 9/1/12 STORM: 1544C INSPECTORS: WH Housing # SITE ID: HWM-MS-HAN-018 LAT (DD to 6 places): 30. 23825 (format: SSS-ST-COU-##PP; see SOP) SITE INFO SITE NAME: Trush line West of Silver Slipper Carino LONG (DD to 6 places): 89. 42 927 STATE: M5 COUNTY: HAN COCK Landowner Info: Notified (Yes/No) Name: SENSOR INFORMATION Sensor Type (circle one): Deployed as (circle one): Data Interval: BP sensor collocated? 30 sec 2 sec Other: Hobo Troll (Yes/No) Water level (WL) Sensor Deploy Time (GMT): **BP Site ID:** RDW **RDG** Baro Pressure (BP) Wave Height (WV) HWM Data Start Time (GMT): HWM Other? USGS VI on housing? Other? Serial # Sensor in Water (Y/N) (Yes/No) Water Surface Reference Point (WSRP) Info Water Surface (WS) Elev. Calculations Reference Point (WSRP) # DETERMINE WATER SURFACE TD Time: GMT Bridge WSRP rail WSRP elevation (feet): 10,620 WSRP elevation (WSRP): feet Elevation Assumed? (Yes/No) A Tapedown (A): WSRP description: Poor Trash line on ponser pale Weight length (B): Total TD (A + B): feet Located West of Carring in parking at Q waters edge Located WS = WSRP - (A + B): feet near 555-M5-HAN-015 WS conditions (circle)? Calm Choppy Wavy Sensor Housing Nut Elevation (D) from WS To determine the Sensor Housing Elevation using Water Surface (WS): DETERMINE THE SENSOR HOUSING ELEVATION a tapeup/tapedown from the established water surface elevation above, use the box to the right. Nut in water? Tape up to nut Choose option! Nut out of water? Tape down: feet D = (WS +/- C) -S:If elevation run to 2nd RP (SHRP) above sensor, then use lower boxes. Sensor Housing Nut Elevation (D) from SHRP SHRP Sensor Housing RP Info SHRP elevation: Reference Point (SHRP) # TD (A + B) Tapedown (A): SHRP elevation (feet): Elevation Assumed? (Yes/No) Weight length (B): feet RP description: Total TD (A + B): Subtract slippage (S): Housing

feet

feet

D = SHRP - (A + B) - S:


slipped

USGS STM SENSOR RECOVERY FORM (page 2)

Sensor Orifice H	levation $(G = D - E)$
Housing Nut (D):	feet
Subtract Housing Correction Factor (E):	feet
Sensor Orifice Elevation (G):	ws T
feet	o G

Use if Sensor Deployed Above Ground w/ no RP Elevation (OEG=D-(H-E)) Housing Nut (D): feet TD to Ground (H): feet Subtract Housing Correction Factor (E): feet Data offset for Depth above Ground (OEG) feet This is used only until RP elevation H is surveyed in to get initial estimate OEG of depth above ground surface

DRAW SITE SKETCH BELOW



RM

IN!!